

Report No.: HTT202109037FR-1

FC TEST REPORT

Product: Development embedded board industrial kits Model: DEBIX Model A Report No.: HTT202109037FR-1 Issued Date: Sep.08,2021

Issued for:

Polyhex Technology Company Limited 5/F, East Zone, Shunheda A2 Building, Liuxiandong Industrial Park, Xili, Nanshan Dist.

Issued by:

Shenzhen HTT Technology Co., Ltd.

1F, B Building, Huafeng International Robotics Industrial Park, Gushu, Xixiang Street, Bao'an District, Shenzhen

Note: This report shall not be reproduced except in full, without the written approval of Shenzhen HTT Technology Co., Ltd. This document may be altered or revised by Shenzhen HTT Technology Co., Ltd. personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.



Report No.: HTT202109037FR-1

TABLE OF CONTENTS

1 TEST RESULT CERTIFICATION	3
2 EUT DESCRIPTION	4
3 TEST METHODOLOGY	5
3.1. DECISION OF FINAL TEST MODE	5
3.2. EUT SYSTEM OPERATION	5
4 SETUP OF EQUIPMENT UNDER TEST	6
4.1. DESCRIPTION OF SUPPORT UNITS	6
5 FACILITIES AND ACCREDITATIONS	7
5.1. FACILITIES	7
5.2. ACCREDITATIONS	7
5.3. MEASUREMENT UNCERTAINTY	7
6 CONDUCTED EMISSION MEASUREMENT	8
6.1. LIMITS OF CONDUCTED EMISSION MEASUREMENT	8
6.2. TEST INSTRUMENTS	8
6.3. TEST PROCEDURES	9
	10
	10
7 RADIATED EMISSION MEASUREMENT	11
7.1. LIMITS OF RADIATED EMISSION MEASUREMENT	11
	11
7.3. TEST PROCEDURES	12
	14
	14 17
	17

HTT

Shenzhen HTT Technology Co., Ltd. TEST RESULT CERTIFICATION

Report No.: HTT202109037FR-1

Product:Development embedded board industrial kitsModel:DEBIX Model AApplicant:Polyhex Technology Company Limited
5/F, East Zone, Shunheda A2 Building, Liuxiandong Industrial Park, Xili, Nanshan Dist.Factory:Polyhex Technology Company Limited
5/F, East Zone, Shunheda A2 Building, Liuxiandong Industrial Park, Xili, Nanshan Dist.Trade Mark:DEBIX

Tested: Sep.02,2021~Sep.08,2021

EMISSION							
Standard Item Result Remarks							
FCC CFR Title 47 Part 15	Conducted (Main Port)	N/A	Meet Class B limit				
Subpart B:2017	Radiated	Pass	Meet Class B limit				
	and the state of t		f				

Note: 1. The test result judgment is decided by the limit of measurement standard 2. The information of measurement uncertainty is available upon the customer's request.

Deviation from Applicable Standard

None

The above equipment has been tested by Shenzhen HTT Technology Co., Ltd. and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Tested By: Ervin Ju check By: Bruce 2hu Approved By: Kein Yong Date: Sep.08,2021 Date: Sep.08,2021 Date: Sep.08.2021 (Kevin Page 3 of 18 Hotline: 400-6655-351 Tel: 0755-23595200 Fax: 0755-23595201 http://www.httprc.com

нтт,

Shenzhen HTT Technology Co., Ltd.

Report No.: HTT202109037FR-1

2 EUT DESCRIPTION

Product	Development embedded board industrial kits		
Model	DEBIX Model A		
Trade Mark	DEBIX		
Applicant	Polyhex Technology Company Limited		
ЕUT Туре	 Engineering Sample. Product Sample, Mass Product Sample. 		
Serial Number	N/A		
Power Rating	DC5V, 3A, 15W		
Data Line	N/A		

I/O PORT

I/O PORT TYPES	Q'TY	TESTED WITH
N/A	N/A	N/A

Model list and Models difference

No.	Model Number	Tested With
1	DEBIX Model A	\boxtimes
	DEBLY Model A is tested model, other models are derivative	models. The models

NOTE: DEBIX Model A is tested model, other models are derivative models, The models are identical in circuit, only different on the model names, size, So the test data of DEBIX Model A can represent the remaining models.



3 TEST METHODOLOGY

3.1. DECISION OF FINAL TEST MODE

The EUT was tested together with the thereinafter additional components, and a configuration, which produced the worst emission levels, was selected and recorded in this report.

The following test mode(s) were scanned during the preliminary test:

Pre-Test Mode			
Emission	Conducted Emission	Mode: Working	
	Radiated Emission	Mode: Working	

After the preliminary scan, the following test mode was found to produce the highest emission level.

The Worst Test Mode			
Emission	Conducted Emission	Mode: Working	
Emission	Radiated Emission	Mode: Working	

Then, the EUT configuration and cable configuration of the above highest emission mode was chosen for all final test items.

3.2. EUT SYSTEM OPERATION

- 1. Set up EUT with the relative support equipments.
- 2. Make sure the EUT worked normally during the test.



4 SETUP OF EQUIPMENT UNDER TEST

4.1. DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

N	. Equipment	Model No.	Serial No.	FCC ID	Trade Name	Data Cable	Power Cord
	N/A	N/A	N/A	N/A	N/A	N/A	N/A

Note:

- 1) All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
- 2) Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.



Report No.: HTT202109037FR-1

5.1. FACILITIES

All measurement facilities used to collect the measurement data are located at HTT

The sites are constructed in conformance with the requirements of ANSI C63.4 and CISPR Publication 22. All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

5.2. ACCREDITATIONS

Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025.

USA	FCC
	ТІМСО
Japan	VCCI
Canada	INDUSTRY CANADA
Germany	TUV
	EMCC

5.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement		Frequency	Uncertainty		
Conducted emissions	150kHz~30MHz		150kHz~30MHz		+/- 3.59dB
Radiated emissions	Horizoptol	Jarizantal 30MHz ~ 200MHz +/			
	HONZONIA	200MHz ~1000MHz	+/- 4.93dB		
	Martical	30MHz ~ 200MHz	+/- 5.04dB		
	venicai	200MHz ~1000MHz	+/- 4.93dB		

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



6 CONDUCTED EMISSION MEASUREMENT

6.1. LIMITS OF CONDUCTED EMISSION MEASUREMENT

	Class A (dBuV)		Class B (dBuV)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 - 0.5	79	66	66 - 56	56 - 46
0.50 - 5.0	73	60	56	46
5.0 - 30.0	73	60	60	50

NOTE:

(1) The lower limit shall apply at the transition frequencies.

(2) The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.

(3) All emanations from EUT or system shall not exceed the level of field strengths specified above.

6.2. TEST INSTRUMENTS

Conducted Emission Shielding Room Test Site 843						
Name of Equipment Manufacturer Model Serial Number Calibration da						
EMI Test Receiver	ROHDE&SCHWARZ	ESCI	100005	06/09/2021		
LISN	AFJ	LS16	16010222119	06/09/2021		
LISN	Meestec	AN3016	04/10040	06/09/2021		

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to International system of unit (SI).

2. N.C.R = No Calibration Request.



6.3. TEST PROCEDURES

Procedure of Preliminary Test

The EUT and Support equipment, if needed, was set up as per the test configuration to simulate typical usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.4 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor standing equipment, it is placed on the ground plane, which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.

All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.

The EUT test program was started. Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.

The Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.

During the above scans, the emissions were maximized by cable manipulation.

The test mode(s) described in Item 3.1 were scanned during the preliminary test.

After the preliminary scan, we found the test mode described in Item 3.1 producing the highest emission level.

The EUT configuration and worse cable configuration of the above highest emission levels were recorded for reference of the final test.

Procedure of Final Test

EUT and support equipment were set up on the test bench as per the configuration with highest emission level in the preliminary test.

A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.

The test data of the worst-case condition(s) was recorded.



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

6.5. TEST RESULTS

N/A



Report No.: HTT202109037FR-1

7 RADIATED EMISSION MEASUREMENT

7.1. LIMITS OF RADIATED EMISSION MEASUREMENT

Maximum permissible level of Radiated Emission measured at 3 meter

FREQUENCY (MHz)	dBuV/m (At 3m)		
	Class B		
30~88	40.00		
88~216	43.50		
216~960	46.00		
960~1000	54.00		

NOTE: (1) The lower limit shall apply at the transition frequencies.

(2) Emission level (dBuV/m) = 20 log Emission level (uV/m).

7.2. TEST INSTRUMENTS

Radiated Emission Test Site 966							
Name of Equipment Manufacturer M		Model	Serial Number	Calibration date			
EMI Test Receiver	ROHDE&SCHWARZ	ESCI	100005	06/09/2021			
Spectrum Analyzer	R&S	FSU	100114	06/09/2021			
Pre Amplifier	H.P.	HP8447E	2945A02715	06/09/2021			
Bilog Antenna	SUNOL Sciences	JB3	A021907	06/09/2021			
Cable	TIME MICROWAVE	LMR-400	N-TYPE04	06/09/2021			
System-Controller	CCS	N/A	N/A	N.C.R			
Turn Table	CCS	N/A	N/A	N.C.R			
Antenna Tower	CCS	N/A	N/A	N.C.R			

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to International system of unit (SI).

2. N.C.R = No Calibration Request.



7.3. TEST PROCEDURES

Procedure of Preliminary Test

The equipment was set up as per the test configuration to simulate typical usage per the user's manual. When the EUT is a tabletop system, a wooden turntable with a height of 0.8 meters is used which is placed on the ground plane. When the EUT is a floor standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.

Support equipment, if needed, was placed as per ANSI C63.4.

All I/O cables were positioned to simulate typical usage as per ANSI C63.4.

Mains cables, telephone lines or other connections to auxiliary equipment located outside the test are shall drape to the floor, be fitted with ferrite clamps or ferrite tubes placed on the floor at the point where the cable reaches the floor and then routed to the place where they leave the turntable. No extension cords shall be used to mains receptacle.

The antenna was placed at 3 meter away from the EUT as stated in ANSI C63.4. The antenna connected to the Spectrum Analyzer via a cable and at times a pre-amplifier would be used.

The Analyzer / Receiver quickly scanned from 30MHz to 1000MHz. The EUT test program was started. Emissions were scanned and measured rotating the EUT to 360 degrees and positioning the antenna 1 to 4 meters above the ground plane, in both the vertical and the horizontal polarization, to maximize the emission reading level.

The test mode(s) described in Item 3.1 were scanned during the preliminary test:

After the preliminary scan, we found the test mode described in Item 3.1 producing the highest emission level.

The EUT and worse cable configuration, antenna position, polarization and turntable position of the above highest emission level were recorded for the final test.

When measuring emissions above 1GHz, the frequencies of maximum emission shall be determined by manually positioning the antenna close to the EUT and by moving the antenna over all sides of the EUT while observing a spectral display. It will be advantageous to have prior knowledge of the frequencies of emissions above 1GHz. If the EUT is a device with dimensions approximately equal to that of the measurement antenna beam width, the measurement antenna shall be aligned with the EUT.



Report No.: HTT202109037FR-1

EUT and support equipment were set up on the turntable as per the configuration with highest emission level in the preliminary test.

The Analyzer / Receiver scanned from 30MHz to 1000MHz. Emissions were scanned and measured rotating the EUT to 360 degrees, varying cable placement and positioning the antenna 1 to 4 meters above the ground plane, in both the vertical and the horizontal polarization, to maximize the emission reading level.

Recorded at least the six highest emissions. Emission frequency, amplitude, antenna position, polarization and turntable position were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit and only Q.P. reading is presented.

For the measurement above 1GHz, use the cable, EUT arrangement, and mode of operation determined in the exploratory testing to produce the emission that has the highest amplitude relative to the limit.

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the antenna in the "cone of radiation" from that area and pointed at the area both in azimuth and elevation, with polarization oriented for maximum response.

The antenna may have to be higher or lower than the EUT, depending on the EUT's size and mounting height, but the antenna should be restricted to a range of height of from 1m to 4m above the ground or reference ground plane.

If the transmission line for the measurement antenna restricts its range of height and polarization, the steps needed to ensure the correct measurement of the maximum emissions, shall be described in detail in the report of the measurements.

using the procedures above to measure with peak detector function, if the result comply with the average limit specified by the appropriate regulation, record the EUT arrangement, mode of operation, and cable positions used for final radiated emission measurement, this can be done with either diagrams or photographs.

Set the detector function of the measuring instrument to average mode, using the procedures above and remeasure only those emissions that complied with the peak limits but exceeded the average limits.

Recorded at least the six highest emissions.



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

7.5. TEST RESULTS

Test Mode	Working	Environmental Conditions	26°C, 55% RH
6dB Bandwidth	120 KHz	Antenna Pole	Vertical / Horizontal
Antenna Distance	3m	Detector Function	Peak / Quasi-peak
Test Result	Pass		

Freq. = Emission frequency in MHz Reading level (dBuV) = Receiver reading Corr. Factor (dB) = Antenna factor + Cable loss Measurement (dBuV) = Reading level (dBuV) + Corr. Factor (dB) Limit (dBuV) = Limit stated in standard Margin (dB) = Measurement (dBuV) – Limits (dBuV)

Report No.: HTT202109037FR-1



Page 15 of 18 Hotline: 400-6655-351 Tel: 0755-23595200 Fax: 0755-23595201 http://www.httprc.com

Report No.: HTT202109037FR-1





Report No.: HTT202109037FR-1







Report No.: HTT202109037FR-1



